

JAPAN TECHNOLOGY

Made More Premium.
Smaller and More Efficient.

HITACHI

Now with



FrostWash™
Self-Cleaning Function

KILLS
99% VIRUSES
99% BACTERIA
95% MOLDS

3-STEP
SELF-CLEANING
PROCESS



RA-08HVK
• 0.8 HP
• 9,000 kJ/h (2.50 kW)
• 560 x 375 x 740 mm (WxHxD)
• CSPF 4.80



RA-10HVK
• 1.0 HP
• 10,600 kJ/h (2.94 kW)
• 560 x 375 x 740 mm (WxHxD)
• CSPF 4.70



RA-15HVK
• 1.5 HP
• 13,000 kJ/h (3.61 kW)
• 560 x 375 x 740 mm (WxHxD)
• CSPF 4.52



RA-20HV
• 2.0 HP
• 18,600 kJ/h (5.17 kW)
• 680 x 468 x 840 mm (WxHxD)
• CSPF 4.45



RA-23HV
• 2.3 HP
• 22,500 kJ/h (6.25 kW)
• 680 x 468 x 840 mm (WxHxD)
• CSPF 4.40



NO-NOISE OPERATION
delivers optimal cooling performance silently.



BODY COMFORT FUNCTION
Calculates the room's comfort index and adjusts humidity and temperature automatically until it is reached



DUAL FAN MOTORS
are alternately assigned to the evaporator and the condenser for even better efficiency of operation.



AUTO-SWING BLADES
instantaneously adjust air deflectors for extended cooling reach.



USER-FRIENDLY REMOTE CONTROL
is designed for easy operation, so you get stress-free cooling convenience without fuss.



VERSATILE MODE SETTINGS
simplify shifting from COOL (on hot days) to FAN (for better air circulation) to DRY (to dehumidify on damp, rainy days)



5-STAR EFFICIENCY RATING
guarantees government-certified maximum energy efficiency, i.e. optimum cooling comfort with the least possible wattage



STYLISH, MODERN DESIGN
is with a classic silvery matte front-panel color that fits perfectly any interior design theme



SELF-DIAGNOSE FUNCTION
automatically detects and identifies any malfunction in real time.



DC PAM INVERTER TECHNOLOGY
manages the unit's operating frequency to keep an optimized temperature setting and maximized cooling efficiency



POWERFUL FUNCTION
for faster, full-on cooling operation with both compressor and fan running at maximum speed.



R410A REFRIGERANT
is the globally accepted refrigerant R410A with very low global warming potential.

OTHER FEATURES:

- Room Temperature Adjustment
- Sleep, Timer and Lock Settings
- Easily Detachable Filter
- Five-Year Warranty for Compressor
- One-Year Warranty for Parts and Service
- Speed of control HI-Med-Lo

MODEL	HORSEPOWER	INPUT POWER	STAR RATING	MONTHLY ENERGY CONSUMPTION	DIMENSIONS	WEIGHT	INSTALLATION DIMENSIONS	CAPACITY	POWER INPUT	RUNNING CURRENT	ENERGY EFFICIENCY
	HP	V		KWH	WXHXD (MM)	KG	WXH(MM)	KJ/H (KW)	WATTS (STD/MAX)	AMPS (STD/MAX)	EER (CSPF)
RA-08HVK	0.8	230 VOLTS/ SINGLE PHASE/ 60HZ	*****	100.85	560 X 375 X 740	42	580 X 410	9,000 (2.50)	747 / 827	3.75 / 4.08	4.80
RA-10HVK	1.0	230 VOLTS/ SINGLE PHASE/ 60HZ	*****	124.47	560 X 375 X 740	42	580 X 410	10,600 (2.94)	922 / 1,042	4.49 / 5.00	4.70
RA-15HVK	1.5	230 VOLTS/ SINGLE PHASE/ 60HZ	*****	163.08	560 X 375 X 740	42	580 X 410	13,000 (3.61)	1,208 / 1,357	5.65 / 6.30	4.52

MODEL	HORSEPOWER	INPUT POWER	STAR RATING	MONTHLY ENERGY CONSUMPTION	DIMENSIONS	WEIGHT	INSTALLATION DIMENSIONS	CAPACITY	POWER INPUT	RUNNING CURRENT	ENERGY EFFICIENCY
	HP	V		KWH	WXHXD (MM)	KG	WXH(MM)	KJ/H (KW)	WATTS	AMPS	EER (CSPF)
RA-20HV	2.0	230 VOLTS/ SINGLE PHASE /60HZ	*****	213.30	680 X 468 X 840	65	700 X 478	18,600 (5.17)	1,580 / 1,948	4.50 / 8.89	4.45
RA-23HV	2.3	230 VOLTS/ SINGLE PHASE /60HZ	*****	278.10	680 X 468 X 840	65	700 X 478	22,500 (6.25)	2,060 / 2,503	9.30 / 11.44	4.40

Window Inverter Series (Compact)



Compact Window Type with Full DC Inverter (RA-HVQC)



RA-08HVQC

- 0.8 HP
- 8,500 kJ/h (2.36 kW)
- 470 x 340 x 600 mm (WxHxD)
- CSPF 4.11



RA-10HVQC

- 1.0 HP
- 9,550 kJ/h (2.65 kW)
- 470 x 340 x 600 mm (WxHxD)
- CSPF 4.02

MODEL	HORSEPOWER	INPUT POWER	STAR RATING	MONTHLY ENERGY CONSUMPTION	DIMENSIONS	WEIGHT	INSTALLATION DIMENSIONS	CAPACITY	POWER INPUT	RUNNING CURRENT	ENERGY EFFICIENCY
	HP	V		KWH	WXHXD (MM)	KG	WXH(MM)	KJ/H (KW)	WATTS (STD/MAX)	AMPS (STD/MAX)	EER (CSPF)
RA-08HVQC	0.8	230 VOLTS/SINGLE PHASE/60HZ	★★★★★	107.06	470 X 340 X 600	29	490 X 350	8,500 (2.36)	793 / 933	3.90 / 4.52	4.11
RA-10HVQC	1.0	230 VOLTS/SINGLE PHASE/60HZ	★★★★★	118.26	470 X 340 X 600	29	490 X 350	9,550 (2.65)	876 / 1,225	4.30 / 5.70	4.02

Compact Window Type Inverter (RA-HSVC)



RA-06HSVC

- 0.6 HP
- 7,000 kJ/h (1.94 kW)
- 470 x 340 x 600 mm (WxHxD)
- CSPF 3.85



RA-08HSVC

- 0.8 HP
- 8,500 kJ/h (2.36 kW)
- 470 x 340 x 600 mm (WxHxD)
- CSPF 3.83



RA-10HSVC

- 1.0 HP
- 9,550 kJ/h (2.65 kW)
- 470 x 340 x 600 mm (WxHxD)
- CSPF 4.01

MODEL	HORSEPOWER	INPUT POWER	STAR RATING	MONTHLY ENERGY CONSUMPTION	DIMENSIONS	WEIGHT	INSTALLATION DIMENSIONS	CAPACITY	POWER INPUT	RUNNING CURRENT	ENERGY EFFICIENCY
	HP	V		KWH	WXHXD (MM)	KG	WXH(MM)	KJ/H (KW)	WATTS (STD/MAX)	AMPS (STD/MAX)	EER (CSPF)
RA-06HSVC	0.6	230 VOLTS/SINGLE PHASE/60HZ	★★★★★	90.72	470 X 340 X 600	29	490 X 350	7,000 (1.94)	672 / 736	3.48 / 3.73	3.85
RA-08HSVC	0.8	230 VOLTS/SINGLE PHASE/60HZ	★★★★★	107.33	470 X 340 X 600	29	490 X 350	8,500 (2.36)	795 / 956	3.58 / 4.60	3.83
RA-10HSVC	1.0	230 VOLTS/SINGLE PHASE/60HZ	★★★★★	130.01	470 X 340 X 600	29	490 X 350	9,550 (2.65)	963 / 1,104	4.57 / 5.16	4.01

Window Deluxe (Conventional)



POWERFUL FUNCTION

AUTO SWING



RA-06SR

- 0.6 HP
- 6,400 kJ/hn (1.78 kW)
- 470 x 340x600 (WxHxD)
- CSPF 3.32



RA-08SR

- 0.8 HP
- 8,800 kJ/hn (2.44 kW)
- 470 x 340x600 (WxHxD)
- CSPF 3.20



RA-10SR

- 1.0 HP
- 9,700 kJ/hn (2.69 kW)
- 470 x 340x600 (WxHxD)
- CSPF 3.08



RA-15SR

- 1.5 HP
- 12,800 kJ/hn (3.56 kW)
- 600 x 400x795 (WxHxD)
- CSPF 3.43



RA-20SR

- 2.0 HP
- 19,100 kJ/hn (5.31 kW)
- 600 x 400x795 (WxHxD)
- CSPF 2.90

MODEL	HORSEPOWER	INPUT POWER	STAR RATING	MONTHLY ENERGY CONSUMPTION	DIMENSIONS	WEIGHT	INSTALLATION DIMENSIONS	CAPACITY	POWER INPUT	RUNNING CURRENT	ENERGY EFFICIENCY
	HP	V		KWH	WXHXD (MM)	KG	WXH(MM)	KJ/H (KW)	WATTS	AMPS	EER (CSPF)
RA-06SR	0.6	230 VOLTS/SINGLE PHASE/60HZ	★★★★★	124.63	470 X 340 X 600	28	490 X 350	6,400 (1.78)	577	2.6	3.32
RA-08SR	0.8	230 VOLTS/SINGLE PHASE/60HZ	★★★★★	162.43	470 X 340 X 600	30	490 X 350	8,800 (2.44)	770	3.3	3.20
RA-10SR	1.0	230 VOLTS/SINGLE PHASE/60HZ	★★★★★	193.97	470 X 340 X 600	31	490 X 350	9,700 (2.69)	898	4.0	3.08
RA-15SR	1.5	230 VOLTS/SINGLE PHASE/60HZ	★★★★★	246.89	600 X 400 X 795	52	620 X 410	12,800 (3.56)	1,143	5.1	3.43
RA-20SR	2.0	230 VOLTS/SINGLE PHASE/60HZ	★★★★★	412.56	600 X 400 X 795	56	620 X 410	19,100 (5.31)	1,910	8.6	2.90

